


Bluetooth LE Module

ME54BS61



Datasheet

V 1.0.0



Version Note

Version	Details	Contributor(s)	Date	Notes
1.0.0	First edit	Michelle	2025.06.23	

Part Number

Model	Hardware Code
ME54BS61	4Y15TE

Click the icon to view and download the latest product documents electronically.
https://en.minewsemi.com/file/ME54BS61-nRF54L15_Datasheet_K_EN.pdf



ME54BS61-nRF54L15

Ultra-Small Size, Ultra-Low Power Consumption, BLE 6.0 Supported Bluetooth Module

The ME54BS61 is a highly flexible, ultra-low power consumption, cost-effective, and compact-sized Bluetooth module based on the nRF54L15 WLCSP. It features a powerful Arm® Cortex®-M33 CPU with a core operating speed of up to 128MHz, along with 1.5MB of NVM space and 256 KB of RAM. The module features 30 GPIO pins for versatile connectivity, and an RF pin for flexible antenna design. Its ultra-low system power consumption, excellent RF performance, and powerful supporting resources make it an ideal solution for Bluetooth connectivity.

FEATURES



Bluetooth 6.0



Ultra-small size



Ultra-low
Power



Multi-Protocol supports:
Bluetooth LE 6.0 Channel
Sounding, Bluetooth Mesh,
Thread, Matter, and proprietary
2.4 GHz protocols

KEY PARAMETER

ME54BS61			
Chip Model	nRF54L15	Antenna	RF PIN
Module Size	6.0×6.0×1.8mm	GPIO	30
Flash	1.5MB	RAM	256 KB
Receiving Sensitivity	-96dBm	Transmission Power	-40~+8dBm
Current(TX)	0dBm-5mA	Current(RX)	3.2mA


APPLICATION



Smart Home



Computer Accessories




Virtual reality and Augmented reality



Game controllers and Remotes



Medical Devices




Industrial IoT




INDEX

1.Block Diagram	05
2.Electrical Specification	05
3.Pin Description	06
4.Pin Definition	06
5.Mechanical Drawing	07
6.Electrical Schematic	07
7.PCB Layout	08
8.Reflow and Soldering.....	08
9.Package Information	09
10.Storage Conditions	10
11.Handling Conditions.....	10
12.Quality	10
13.Copyright Statement.....	11
14.Related Documents	11



1

BLOCK DIAGRAM




2

ELECTRICAL SPECIFICATION

Parameter	Values	Notes
Working Voltage	1.7V-3.6V	To ensure proper RF performance, it is recommended that the supply voltage is not lower than 2.3V
Working Temperature	-40℃~+105℃	Operating temperature from -40℃ to 105℃
Transmission Power	-40~+8dBm	Configurable
Current(RX)	3.2mA	RF receiving current under 1Mbps pattern
Current(TX)	5mA	RF transmission current under 0dBm pattern
Module Dimension	6.0*6.0*1.8mm	
Quantity of IO Port	30	


3PIN DESCRIPTION



4PIN DEFINITION


Pin Number	Symbol	Type	Definition
A1	RF	External Antenna	Connect external antenna via this pin
A2/B1/D2/E7/G3	GND	GND	Ground
D7	VCC	Power Supply	
B3	SWDIO	Programming Data	Used for firmware programming
B4	SWCLK	Programming Clock	Used for firmware programming
C2	RST	Reset	Low level reset, high level operation
A3-A7	P2.04/P2.05/P2.03/P2.01/P2.00	GPIO	General-purpose IO
B2/B5-B7	P2.06/P2.02/P1.07/P1.08	GPIO	General-purpose IO
C1/C6 C7	P0.00/P1.03/P1.06	GPIO	General-purpose IO
D1/D6	P0.01/P1.02	GPIO	General-purpose IO
E1/E2 E6	P0.02/P2.10/P1.04	GPIO	General-purpose IO
F1-F7	P0.03/P2.09/P2.08/P1.09/P1.11/P1.14/P1.05	GPIO	General-purpose IO
G1-G7	P0.04/P2.07/P1.10/P1.12/P1.13/P1.15	GPIO	General-purpose IO

5 MECHANICAL DRAWING



Default unit: mm Default tolerance: ±0.15

6 ELECTRICAL SCHEMATIC



Notice: Before placing an order, please confirm the specific configuration required with the salesperson.

7 PCB LAYOUT


There should be no GND plane or metal cross wiring in the module antenna area, and no components should be placed nearby. It is best to make a hollow or clear area, or place it on the edge of the PCB board. The reference example is as follows:



Notice: It is strongly recommended to use the first design method. The module antenna design is debugged according to the first wiring.


Layout Notes:

- 1) The module's antenna area should be completely clear of any metal obstructions to avoid affecting antenna performance (as shown in the diagram).
- 2) Outside the module's antenna area, try to maintain a solid copper pour to minimize interference from the mainboard signal lines or other sources.
- 3) A clear area of at least 4mm should surround the module's antenna (including its casing) to reduce interference with the antenna.
- 4) Ensure good grounding for components to minimize parasitic inductance.
- 5) Do not place copper under the module's antenna to prevent interference with signal radiation, which could affect transmission distance.
- 6) The antenna should be kept away from other circuits to maintain radiation efficiency and avoid impacting the normal operation of other circuits.
- 7) Position the module as close to the edge of the circuit board as possible, away from other circuitry.
- 8) It is recommended to use a ferrite bead for isolation when connecting the module to the power supply.




8 REFLOW AND SOLDERING

- 1) Perform SMT according to the reflow oven temperature profile provided below, with a maximum temperature of 260°C;
- 2) Follow IPC/JEDEC standards; Peak temperature: < 260°C; Number of reflows: ≤ 2 times; For SMT involving double-sided placement, it is recommended that the module side undergoes reflow soldering only once. For any special processes, please contact our company.
- 3) Module SMT recommended stencil thickness 0.1-0.12mm, pin 1:0.9 opening, not expanded;
- 4) After opening, if the entire package is not used at once, it should be stored in a vacuum to prevent long-term exposure to air, which can cause moisture absorption and pad oxidation. If there is a gap of 7 to 30 days before reuse, it is recommended to bake the tape at 65-70°C for 24 hours without unrolling it before returning to SMT.
- 5) ESD protection measures should be implemented before using SMT.




9 PACKAGE INFORMATION




Remarks

General material list for FCL packaging:



Carrier tape packaging tray



Humidity Indicator
(1 pcs/bag)



Desiccant
(placed in a vacuum bag)



Vacuum bag



Inner carton(*8)
355*345*35mm, ±5mm



Outer carton
370*358*350mm, ±10mm

Other:

Moisture-proof label (attached to the vacuum bag)

Certification label (attached to the vacuum bag)

Outer box label



Default unit: mm Default tolerance: ± 0.1

Packing detail	Specification	Net weight	Gross weight	Dimension
ME54BS61	1900PCS	TBD	TBD	W=24mm, T=0.30mm



Note: Default weight tolerance all are within 10g (except the special notes)

10 STORAGE CONDITIONS

- Please use this product within 6 months after signing the receipt.
 - This product should be stored without opening the package at an ambient temperature of 5~35°C and a humidity of 20~70%RH.
 - This product should be left for more than 6 months after receipt and should be confirmed before use.
 - The product must be stored in a non-corrosive gas (Cl₂, NH₃, SO₂, NO_x, etc.).
 - To avoid damaging the packaging material, do not apply any excessive mechanical shocks, including but not limited to sharp objects adhering to the packaging material and product dropping.
- This product is suitable for MSL2 (based on JEDEC standard J-STD-020).
 - After opening the package, the product must be stored at ≤30°C/<60%RH. It is recommended to use the product within 3-6 months after opening the package.
 - When the color of the indicator in the package changes, the product should be baked before welding.
- Baking is not required for one year if exposure is limited to <30°C and 60%RH. Refer to MSL2 for exposure criteria for moisture sensitivity level. If exposed to (≥168h@85°C/60%RH) conditions or stored for more than one year, recommended baking conditions.
 1. 120 ±5/-5°C, 8 hours, 1 timeProducts must be baked individually on heat-resistant trays because the materials (base tape, reel tape, and cover tape) are not heat-resistant, and the packaging material may be deformed at temperatures of 120 °C;
 2. 90 °C ±8/-0 °C, 24hours, 1timesThe base tape can be baked together with the product at this temperature. Please pay attention to the uniformity of heat.

11 HANDLING CONDITIONS

- Be careful in handling or transporting products because excessive stress or mechanical shock may break products.
- Handle with care if products may have cracks or damages on their terminals. If there is any such damage, the characteristics of products may change. Do not touch products with bare hands that may result in poor solder ability and destroy by static electrical charge.

12 QUALITY

Cognizant of our commitment to quality, we operate our own factory equipped with state-of-the-art production facilities and a meticulous quality management system. We hold certifications for ISO9001, ISO14001, ISO27001, OHSAS18001, BSCI.

Every product undergoes stringent testing, including transmit power, sensitivity, power consumption, stability, and aging tests. Our fully automated module production line is now in full operation, boasting a production capacity in the millions, capable of meeting high-volume production demands.

13 COPYRIGHT STATEMENT

This manual and all the contents contained in it are owned by Shenzhen Minewsemi Co., Ltd. and are protected by Chinese laws and applicable international conventions related to copyright laws.

The certified trademarks included in this product and related documents have been licensed for use by MinewSemi. This includes but is not limited to certifications such as BQB, RoHS, REACH, CE, FCC, BQB, IC, SRRC, TELEC, WPC, RCM, WEEE, etc. The respective textual trademarks and logos belong to their respective owners. For example, the Bluetooth® textual trademark and logo are owned by Bluetooth SIG, Inc. Other trademarks and trade names are those of their respective owners. Due to the small size of the module product, the "®" symbol is omitted from the Bluetooth Primary Trademarks information in compliance with regulations.

The company has the right to change the content of this manual according to the technological development, and the revised version will not be notified otherwise. Without the written permission and authorization of the company, any individual, company, or organization shall not modify the contents of this manual or use part or all of the contents of this manual in other ways. Violators will be held accountable in accordance with the law.

14 RELATED DOCUMENTS

- [MinewSemi_Product_Naming_Reference_Manual](https://en.minewsemi.com/file/MinewSemi_Product_Naming_Reference_Manual_EN.pdf)
https://en.minewsemi.com/file/MinewSemi_Product_Naming_Reference_Manual_EN.pdf
- [MinewSemi_Connectivity_Module_Catalogue](https://en.minewsemi.com/file/MinewSemi_Connectivity_Module_Catalogue_EN.pdf)
https://en.minewsemi.com/file/MinewSemi_Connectivity_Module_Catalogue_EN.pdf



For product change notifications and regular updates of Minewsemi documentation, please register on our website: www.minewsemi.com

MINESEMI

SHENZHEN MINEWSEMI CO., LTD.



0086-755-2801 0353

<https://minewsemi.com>minewsemi@minew.com<https://store.minewsemi.com>

No.8, Qinglong Road, Longhua District, Shenzhen, China